

27" P-cap Touch Monitor



H2712P-UH

Touch Technology

P-cap

Version

V 1.1



Product specification

Product Name		27 inch LCD Touch Monitor		
Product Model		H2712P-UH		
LCD panel Technical Parameter	Size	27 inch		
	Aspect Ratio	16 : 9		
	Backlight Type	LED Backlight		
	Pixel Pitch	0.3114mm x 0.3114mm		
	Active Area	597.888mm x 336.312mm		
	Best Resolution	1920 × 1080 @ 60 Hz		
	Response Time	14 ms		
	Color	16.7 million		
	Brightness	LCD Panel: 300 cd/m ²		
	Contrast Ratio	1000:1 (standard Values)		
	Viewing Angle (CR > 10)	Horizontal: 178° (89°/89°) Vertical: 178° (89°/89°)		
	Video Input Format	RGB Analog Signal/ Digital Signal		
	Video Input Interface	VGA / DVI / HDMI		
	Input Frequency	Horizontal: 30~82 Hz Vertical: 50~75 Hz		
	Power Consumption	≤24W		
Warranty	1 Year			
Touch Screen Technical Parameter	Touch Screen Type	Capacitive Touch Screen		
	Cover Glass	Tempered Glass 3mm		
	Transparency	87%		
	Hardness	7H		
	Interface	USB2.0		
	Touch Point	10		
	Response Time	≤15 ms		
	Touch Method	Finger / Capacitive Pen		
	Touch Lifespan	≥50,000,000		
	Linearity	< 2%		
	Single-point OS	Windows XP , Linux		
	Multi-point OS	Windows7/8 , Android		
	Warranty	1 Year		
Touch Monitor Technical Parameter	Boundary Dimension	654mmx352mmx47.5mm		
	OSD Panel	Optional Accessory : Power switch、Menu、Up、Auto、Down		
	Power Supply	Input : DC 12V±5%		
	Power Consumption	Max : 30w; Sleep : 3w; Off : 2w		
	Installation	VESA 200mm		
	Accessory (Optional)	Signal Line	VGA, HDMI, D-SUB 15 pin, male to male, 1.5m	
		USB Wire	A male to B male , 1.8m	
		Adaptor	WT1203000 ,12V/3.0A ,115mmx47mmx31mm , Length 1.0m , φ 2.5 , Black	
		Power Line	Power Line, 1.5m , Black	
	Temperature	Operating: 0°C-40°C ; Storage: -20°C-60°C		
	Humidity	Operating: 20%-80%; Storage: 10%-90%		
	Operation Altitude	< 3000m		
	Warranty	1Year		



